

Marine 2T Motor Oil

Description

High-performance 2-stroke motor oil based on selected base oils and specially formulated additives. Provides for reliable lubrication, engine reliability and outstanding protection against wear and corrosion. No uncontrolled ignition, low-fuming combustion. With TC-W3-level performance.

Properties

- high lubrication reliability
- high wear resistance
- prevents spontaneous ignition
- self mixing
- residue-free combustion

Specifications and approvals:

API TC • JASO FB

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

NMMA TC-W3

Technical data

Viscosity at 40 °C	54,2 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	8,9 mm ² /s ASTM D 7042-04
Viscosity index	143 DIN ISO 2909
Density at 15 °C	0,875 g/cm ³ DIN 51757
Flash point	106 °C DIN ISO 2592
Pour point	-39 °C DIN ISO 3016
Total base number	9,8 mg KOH/g DIN ISO 3771
Sulfate ash	<0,02 g/100g DIN 51575
Color number (ASTM)	4,0 DIN ISO 2049

Areas of application

For air and water-cooled 2-stroke marine engines with separate and premix lubrication systems. Self-mixing. Please note that the mixture ratio specified by the manufacturer must be observed.



Application

Use as normal for two-stroke oils for mixture and separate lubrication systems. Keep to the mixing ratios stipulated by the relevant engine manufacturer.

Available pack sizes

1 l Canister plastic	25019 BOOKLET
5 l Canister plastic	25020 BOOKLET

Our information is based on thorough research and may be considered reliable, although not legally binding.