



Quality is in our nature

Passenger car engine oils - Fully Synthetic

Eurol Elance 5W-30

Fully synthetic fuel economy engine oil, ACEA C3/C2 and Renault RN17

Description

Eurol Elance 5W-30 is a fully synthetic high performance engine oil for gasoline and diesel vehicles.

Eurol Elance 5W-30 provides an extremely stable lubricant film at the cold start and offers high thermal stability under severe driving operating conditions (motorway and urban traffic). The oil is able to flow and to lubricate critical parts, preventing wear and ensuring engine protection.

Eurol Elance 5W-30 provides maximum protection against rust and corrosion, while the used additive package keeps the engine clean and well lubricated.

Eurol Elance 5W-30 has low sulphated ash contents and also low levels of phosphor and sulphur (so called "mid-SAPS" technology).

Eurol Elance 5W-30 fulfills the requirements of Renault RN17 and can also be used where RN0700 and RN0710 are prescribed.

Specifications

<u>Performance level</u>	VW 505.00
API SN	<u>Recommended for use</u>
ACEA C2	Renault RN0700 / 0710
ACEA C3	
Renault RN17	
VW 505.01	
MB 229.51	
MB 229.52	
MB 229.31	
BMW Longlife-04	
GM dexos 2	

Physical properties

Colour	Brown	
Density at 20°C	0.851 kg/l	ASTM D 1298
Viscosity, kinematic at 40°C	73.2 cSt	ASTM D 445
Viscosity, kinematic at 100°C	12.1 cSt	ASTM D 445
Viscosity Index	163	ASTM D 2270
Viscosity, dynamic (CCS)	5832 cP	ASTM D 2602
Base number	8.0 mg KOH/g	ASTM D 2896
Sulphated ash	0.7 wt%	ASTM D 874
Flash point	192 °C	ASTM D 93
Pour point	-45 °C	ASTM D 97

Available in 5L, 20L, 210L

E100012
Version 1.0, 14-05-2018

This sheet contains recommendations or suggestions on properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical information in this document consists of typical incorrectness of the text. The reader is advised to make the final product choice in dialogue with the supplier.

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, Netherlands, tel. +31 88 250 22 00, fax +31 548 61 01 95, info@eurol.com, www.eurol.com