Product information

PI 30/18/06/2018

Motorbike 4T Synth 5W-40 Street Race



Description

Fully synthetic high-performance motor oil. Ensures maximum performance and protection of the engine under all operating conditions. Optimum lubrication, outstanding engine cleanliness, excellent friction and minimum wear are just as much taken for granted as gentle clutch engagement and disengagement and gear shifting. That makes a big difference to driving enjoyment! Tested on engines with catalytic converters. Tested on racing machines.

Properties

- tested for catalytic converters
- optimum stability to aging
- high engine cleanliness
- guarantees low oil consumption
- optimum lubrication under all operating conditions
- excellent shear stability
- especially suitable for wet clutches
- excellent wear resistance

Specifications and approvals:

ACEA A3 • API SM • JASO MA2

Technical data

recillicat data	
SAE class (engine oils)	5W-40 SAE J300
Density at 15 °C	0,850 g/cm³ DIN 51757
/iscosity at 40 °C	90.2 mm²/s ASTM D 7042-04
/iscosity at 100 °C	14,5 mm²/s ASTM D 7042-04
/iscosity at -35 °C (MRV)	<= 60000 mPas ASTM D4684
/iscosity at -30°C (CCS)	<= 6600 mPas ASTM D5293
/iscosity index	167 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D5481
Pour point	-45 °C DIN ISO 3016
Evaporation loss (Noack)	7.0 % CEC-L-40-A-93
/iscosity at -30°C (CCS) /iscosity index HTHS at 150°C Pour point	ASTM D4684 <= 6600 mPas ASTM D5293 167 DIN ISO 2909 >= 3,5 mPas ASTM D5481 -45 °C DIN ISO 3016 7.0 %



Technical data

Sulfate ash 1,0 - 1,6 g/100g DIN 51575

Color number (ASTM) L4,0

DIN ISO 2049

Areas of application

Developed for air and water-cooled 4-stroke engines exposed to normal to extreme operating conditions. For sporting applications. Suitable for engines with or without a wet clutch.

Application

The operating instructions of the engine manufacturers must be followed.

Note: Optimum effectiveness only when the product is used on its own (i.e. no mixing).

Available pack sizes

Available pack Sizes	
1 l Canister plastic	2592 BOOKLET
1 l Canister plastic	20074 GB-F-E-USA-CAN
1 l Canister plastic	1750 JP
4 l Canister plastic	1685 BOOKLET
4 l Canister plastic	20076 GB-F-E-USA-CAN
20 l Canister plastic	2720 D-GB-I-E-P
20 l Canister plastic	20851 JP
60 l Drum sheet metal	2593 D-GB
205 l Drum sheet metal	2594 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

Flash point

Total base number

230 °C

DIN ISO 2592

DIN ISO 3771

10,5 mg KOH/g