



Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

MSDS Version: E09.00

Date of issue: 07/08/2019

:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Fuel System Cleaner
Product code : W61351

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : Petrol additive.
Function or use category : Lubricants and additives

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Wynn's Belgium
Industriepark-West 46
9100 Sint-Niklaas - Belgium
T +32 3 766 60 20 - F +32 3 778 16 56
msds@wynns.eu - www.wynns.com

1.4. Emergency telephone number

Emergency number : BIG: +32(0)14/58.45.45 (NL FR EN DE)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2	H225
Eye Irrit. 2	H319
STOT RE 2	H373
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02



GHS07



GHS08

Signal word (CLP) : Danger

Hazardous ingredients : hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%);
distillates (Fischer-Tropsch), C8-26, branched and linear

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.
H304 - May be fatal if swallowed and enters airways.
H319 - Causes serious eye irritation.
H373 - May cause damage to organs (central nervous system) through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects.

EUH-statements : EUH066 - Repeated exposure may cause skin dryness or cracking.

Precautionary statements (CLP) : P102 - Keep out of reach of children.
P405 - Store locked up.
P210 - Keep away from hot surfaces, open flames, sparks, heat. No smoking.
P260 - Do not breathe vapours.

Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

P280 - Wear eye protection.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor
P331 - Do NOT induce vomiting.
P273 - Avoid release to the environment.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% w	Classification according to Regulation (EC) No. 1272/2008 [CLP]
distillates (Fischer-Tropsch), C8-26, branched and linear	(CAS-No.) 848301-67-7 (EC-No.) 481-740-5 (REACH-no) 01-0000020119-75	50 - 75	Asp. Tox. 1, H304
Propan-2-ol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0 (REACH-no) 01-2119457558-25	10 - 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
4-methylpentan-2-ol	(CAS-No.) 108-11-2 (EC-No.) 203-551-7 (EC Index-No.) 603-008-00-8 (REACH-no) 01-2119473979-13	5 - 10	Flam. Liq. 3, H226 Eye Irrit. 2, H319 STOT SE 3, H335
1-Propene, 2-methyl-, homopolymer, hydroformylation products, reaction products with ammonia	(CAS-No.) 337367-30-3	2,5 - 5	Skin Irrit. 2, H315 Aquatic Chronic 3, H412
Kerosine (petroleum), hydrodesulfurized	(CAS-No.) 64742-81-0 (EC-No.) 265-184-9 (EC Index-No.) 649-423-00-8 (REACH-no) 01-2119462828-25	2,5 - 5	Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	(EC-No.) 919-164-8 (REACH-no) 01-2119473977-17	2,5 - 5	STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 3, H412
Name	Product identifier	Specific concentration limits	
4-methylpentan-2-ol	(CAS-No.) 108-11-2 (EC-No.) 203-551-7 (EC Index-No.) 603-008-00-8 (REACH-no) 01-2119473979-13	(25 =<C < 100) STOT SE 3, H335	

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Check the vital functions. Keep victim at rest in half upright position. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Keep watching the victim. Give psychological aid. Prevent cooling by covering the victim (no warming up). Keep the victim calm, avoid physical strain. If necessary seek medical advice.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor. Ingestion of large quantities: immediately to hospital.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Tingling/irritation of the skin. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after ingestion	: Abdominal pain. Headache. Harmful if swallowed. Risk of aspiration pneumonia. May be fatal if swallowed and enters airways.

Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Alcohol resistant foam. ABC-powder.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour. Gas/vapour spreads at floor level: ignition hazard. Take precautionary measures against static discharge.

Explosion hazard : Product is not explosive.

5.3. Advice for firefighters

Firefighting instructions : Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

Protective equipment : Wear suitable gloves and eye/face protection. protective clothing.

Emergency procedures : Mark the danger area. Prevent flow to low areas. In confined space use self-contained breathing apparatus. Take off contaminated clothing.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage. Contain leaking substance, pump over in suitable containers.

Methods for cleaning up : Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. Clean preferably with a detergent - Avoid the use of solvents.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Meet the legal requirements. Some components of the product destroy skin oils. Provide good ventilation in process area to prevent formation of vapour. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Presents no particular risk when handled in accordance with good occupational hygiene practice.

Hygiene measures : Use good personal hygiene practices. IF ON SKIN: Gently wash with plenty of soap and water. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Take precautionary measures against static discharge. Does not require any specific or particular technical measures.

Storage conditions : Protect from sunlight. Store in a well-ventilated place. Meet the legal requirements. Keep container tightly closed.

Storage temperature : < 45 °C

Storage area : Meet the legal requirements. Ventilation along the floor.

Special rules on packaging : Keep only in original container. Labelling according to.

7.3. Specific end use(s)

See product bulletin for detailed information.

Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Propan-2-ol (67-63-0)

Belgium	Limit value (mg/m ³)	500 mg/m ³
Belgium	Limit value (ppm)	200 ppm
Belgium	Short time value (mg/m ³)	1000 mg/m ³
Belgium	Short time value (ppm)	400 ppm
France	VLE (mg/m ³)	980 mg/m ³
France	VLE (ppm)	400 ppm

4-methylpentan-2-ol (108-11-2)

Belgium	Limit value (mg/m ³)	106 mg/m ³
Belgium	Limit value (ppm)	25 ppm
Belgium	Short time value (mg/m ³)	169 mg/m ³
Belgium	Short time value (ppm)	40 ppm
Belgium	Remark (BE)	D
France	VME (mg/m ³)	100 mg/m ³
France	VME (ppm)	25 ppm
Germany	Occupational exposure limit value (mg/m ³)	85 mg/m ³
Germany	Occupational exposure limit value (ppm)	20 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	25 ppm
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	40 ppm
United Kingdom	WEL TWA (mg/m ³)	106 mg/m ³
United Kingdom	WEL TWA (ppm)	25 ppm
United Kingdom	WEL STEL (mg/m ³)	170 mg/m ³
United Kingdom	WEL STEL (ppm)	40 ppm

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Belgium	Limit value (mg/m ³)	533 mg/m ³
Belgium	Limit value (ppm)	100 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	100 ppm

distillates (Fischer-Tropsch), C8-26, branched and linear (848301-67-7)

PNEC (Sediment)	
PNEC sediment (freshwater)	2,06 mg/kg dwt
PNEC (Soil)	
PNEC soil	1,68 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	10 mg/l

Propan-2-ol (67-63-0)

DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	888 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	500 mg/m ³
DNEL/DMEL (General population)	
Long-term - systemic effects, oral	26 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	89 mg/m ³
Long-term - systemic effects, dermal	319 mg/kg bodyweight/day
PNEC (Water)	
PNEC aqua (freshwater)	140,9 mg/l
PNEC aqua (marine water)	140,9 mg/l
PNEC aqua (intermittent, freshwater)	140,9 mg/l
PNEC aqua (intermittent, marine water)	140,9 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	552 mg/kg dwt
PNEC sediment (marine water)	552 mg/kg dwt
PNEC (Soil)	

Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Propan-2-ol (67-63-0)

PNEC soil	28 mg/kg dwt
PNEC (Oral)	
PNEC oral (secondary poisoning)	160 mg/kg food
PNEC (STP)	
PNEC sewage treatment plant	2251 mg/l

4-methylpentan-2-ol (108-11-2)

DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	208 mg/m ³
Acute - local effects, inhalation	104 mg/m ³
Long-term - systemic effects, dermal	11,8 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	83 mg/m ³
Long-term - local effects, inhalation	83 mg/m ³
DNEL/DMEL (General population)	
Acute - systemic effects, inhalation	155,2 mg/m ³
Acute - local effects, inhalation	52,1 mg/m ³
Long-term - systemic effects, oral	4,2 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	14,7 mg/m ³
Long-term - systemic effects, dermal	4,2 mg/kg bodyweight/day
Long-term - local effects, inhalation	14,7 mg/m ³
PNEC (Water)	
PNEC aqua (freshwater)	0,6 mg/l
PNEC aqua (marine water)	0,06 mg/l
PNEC aqua (intermittent, freshwater)	3,3 mg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	2,94 mg/kg dwt
PNEC sediment (marine water)	0,3 mg/kg dwt
PNEC (Soil)	
PNEC soil	0,24 mg/kg dwt
PNEC (STP)	
PNEC sewage treatment plant	1 mg/l

8.2. Exposure controls

Appropriate engineering controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide good ventilation in process area to prevent formation of vapour. Does not require any specific or particular technical measures.

Personal protective equipment

: Gloves. Safety glasses.



Hand protection

: Neoprene. Nitrile rubber. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Time of penetration is to be checked with the glove producer.

Other information

: Breakthrough time : >30'. Thickness of the glove material >0,1 mm.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: clear.
Colour	: light yellow.
Odour	: alcohol.
Odour threshold	: No data available
pH	:
Relative evaporation rate (butylacetate=1)	: No data available
refraction index	: 1,43

Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 75 °C
Flash point	: 12 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density @20°C	: 786 kg/m ³
Solubility	: In water, material is partially soluble.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic @40°C	: 2,8 mm ² /s
Viscosity, dynamic @40°C	: No data available
Viscosity	:
Viscosity Index	:
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 93,16 %
Additional information	: The physical and chemical data in this section are typical values for this product and are not intended as product specifications.

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from strong acids and strong oxidizers.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

On burning: release of harmful/irritant gases/vapours. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Harmful: may cause lung damage if swallowed
----------------	---

distillates (Fischer-Tropsch), C8-26, branched and linear (848301-67-7)

LD50 oral rat	> 5000 mg/kg bodyweight Sprague-Dawley
LD50 dermal rat	> 2000 mg/kg bodyweight Sprague-Dawley

Propan-2-ol (67-63-0)

LD50 oral rat	5840 mg/kg bodyweight Sherman
LD50 dermal rabbit	13900 mg/kg bodyweight
LC50 inhalation rat (mg/l)	> 25 mg/l
ATE CLP (oral)	5840 mg/kg bodyweight
ATE CLP (dermal)	13900 mg/kg bodyweight

Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4-methylpentan-2-ol (108-11-2)

LD50 oral rat	2590 mg/kg bodyweight
LD50 dermal rabbit	2870 mg/kg bodyweight
LC50 inhalation rat (mg/l)	> 16 mg/l/4h Wistar
ATE CLP (oral)	2590 mg/kg bodyweight
ATE CLP (dermal)	2870 mg/kg bodyweight

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

LD50 oral rat	> 15000 mg/kg
LD50 dermal rabbit	> 3400 mg/kg
LC50 inhalation rat (mg/l)	> 13,1 mg/l/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs (central nervous system) through prolonged or repeated exposure.
Aspiration hazard	: May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: This product contains hazardous components for the aquatic environment.
Ecology - water	: Harmful to aquatic life with long lasting effects.

distillates (Fischer-Tropsch), C8-26, branched and linear (848301-67-7)

LC50 fish 1	> 1000 mg/l @96h Pimephales promelas
EC50 Daphnia 1	> 1000 mg/l @48h Daphnia magna
EC50 other aquatic organisms 1	> 1000 mg/l @72h Pseudokirchneriella subcapitata
NOEC (acute)	> 1000 mg/l @48h Daphnia magna

Propan-2-ol (67-63-0)

LC50 fish 1	96h 9640 mg/l pimephales promelas
EC50 Daphnia 1	24h 9714 mg/l daphnia magna
LOEC (chronic)	1000 mg/l @8d algae

4-methylpentan-2-ol (108-11-2)

LC50 fish 1	> 92,4 mg/l @96h Pimephales promelas
EC50 Daphnia 1	48h 337 mg/l Daphnia magna
EC50 other aquatic organisms 1	96h 334 mg/l Pseudokirchneriella subcapitata
NOEC (acute)	48h 288 mg/l Daphnia magna

12.2. Persistence and degradability

distillates (Fischer-Tropsch), C8-26, branched and linear (848301-67-7)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

Propan-2-ol (67-63-0)

Persistence and degradability	Readily biodegradable.
-------------------------------	------------------------

4-methylpentan-2-ol (108-11-2)

Persistence and degradability	Readily biodegradable in water. easily degradable in the soil.
-------------------------------	--

12.3. Bioaccumulative potential

distillates (Fischer-Tropsch), C8-26, branched and linear (848301-67-7)

Log Pow	> 6,5 @40°C
---------	-------------

Propan-2-ol (67-63-0)

Log Pow	0,05
Log Kow	< 4

Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Propan-2-ol (67-63-0)

Bioaccumulative potential

No bioaccumulation.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Propan-2-ol (67-63-0)

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Remove to an authorized waste treatment plant. Avoid release to the environment.

European List of Waste (LoW) code : 14 06 03* - other solvents and solvent mixtures
15 01 10* - packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1993

14.2. UN proper shipping name

Proper Shipping Name (ADR) : FLAMMABLE LIQUID, N.O.S.

Transport document description (ADR) : UN 1993 FLAMMABLE LIQUID, N.O.S. (Isopropanol), 3, II, (D/E)

14.3. Transport hazard class(es)

Class (ADR) : 3

Danger labels (ADR) : 3



14.4. Packing group

Packing group (ADR) : II

14.5. Environmental hazards

Other information : No supplementary information available.


14.6. Special precautions for user

14.6.1. Overland transport

Hazard identification number (Kemler No.) : 33

Classification code (ADR) : F1

Orange plates :



Special provisions (ADR) : 274, 601, 640D

Transport category (ADR) : 2

Tunnel restriction code (ADR) : D/E

Limited quantities (ADR) : 1I

Excepted quantities (ADR) : E2

Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EAC code : •3YE

14.6.2. Transport by sea

EmS-No. (1) : F-E, S-E

14.6.3. Air transport

Instruction "cargo" (ICAO) : 364

Instruction "passenger" (ICAO) : 353

Instruction "passenger" - Limited quantities (ICAO) : Y341

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC content : 93,16 %

15.1.2. National regulations

Water hazard class (WGK) : 2 - Significantly hazardous to water

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:

Aquatic Chronic 2

Hazardous to the aquatic environment — Chronic Hazard, Category 2

Aquatic Chronic 3

Hazardous to the aquatic environment — Chronic Hazard, Category 3

Asp. Tox. 1

Aspiration hazard, Category 1

Eye Irrit. 2

Serious eye damage/eye irritation, Category 2

Flam. Liq. 2

Flammable liquids, Category 2

Flam. Liq. 3

Flammable liquids, Category 3

Skin Irrit. 2

Skin corrosion/irritation, Category 2

STOT RE 1

Specific target organ toxicity — Repeated exposure, Category 1

STOT RE 2

Specific target organ toxicity — Repeated exposure, Category 2

STOT SE 3

Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

STOT SE 3

Specific target organ toxicity — Single exposure, Category 3, Narcosis

H225

Highly flammable liquid and vapour.

H226

Flammable liquid and vapour.

H304

May be fatal if swallowed and enters airways.

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H335

May cause respiratory irritation.

H336

May cause drowsiness or dizziness.

H372

Causes damage to organs through prolonged or repeated exposure.

H373

May cause damage to organs through prolonged or repeated exposure.

H411

Toxic to aquatic life with long lasting effects.

Fuel System Cleaner

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.