

Page 1/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 8

Revision: 16.03.2021

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

- · Trade name: BRUNOX® epoxy® BULK
- · UFI: WRGA-YVXS-7206-2WNT

• <u>1.2 Relevant identified uses of the substance or mixture and uses advised against</u>

- Sector of Use
- SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category

PC9a Coatings and paints, thinners, paint removers

PC14 Metal surface treatment products

· Process category

PROC5 Mixing or blending in batch processes

PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

- PROC10 Roller application or brushing
- PROC11 Non industrial spraying
- PROC13 Treatment of articles by dipping and pouring

Environmental release category

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

· Application of the substance / the mixture Coating material

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

BRUNOX Korrosionsschutz GmbH Adlzreiterstrasse 13, 85051 Ingolstadt Postfach 100127, 85001 Ingolstadt

Tel. + 49/ (0) 841 961 29 04 Fax + 49/ (0) 841 961 29 13 E-mail: office@brunox.com

UFI info / E-mail: ufi@brunox.com www.brunox.de

BRUNOX AG Tunnelstrasse 6 CH - 8732 Neuhaus/SG

Tel. +41/ (0)55 285 80 80 Fax +41/ (0)55 285 80 81

E-mail: office@brunox.com www.brunox.swiss UFI info / E-mail: ufi@brunox.com



Page 2/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021 Version number 8 Revision: 16.03.2021
Trade name: BRUNOX® epoxy® - BULK
(Contd. of page 1)

• Further information obtainable from:
Abteilung Produktsicherheit / Product Safety Department:
Tel. - Switzerland: +41/ (0)55 285 80 80
Tel. - Germany: +49 / (0)841 961 29 04
Mo - Do / Mon - Thu: 08:00 - 16:00 Uhr

Fr / Fri: 08:00 - 12:00 Uhr · 1.4 Emergency telephone number: Toxikologisches Informationszentrum CH - 8030 Zürich, Freiestrasse 16 Tel. +41/ 044 251 51 51 Notruf - CH, STIZ : 145 Notruf - D - : Giftnotrufzentrale 030 19240 Notruf - BE - : 070 -245 245 EUROPÄISCHE NOTRUFNR.: 112 Notruf - GB - : 844 892 0111 Notruf - IE - : + 353 1 837 9964 (medical professionals); + 353 1 809 2166 (public) Notruf - IS - : + 354 543 22 22 Notruf - JP - : + 81 72 727 2499; + 81 29 852 9999 Notruf - NZ - : 0800 764 766 Notruf - PK - : + 92 21 9920509; + 92 21 35686535 Notruf - PH - : + 632 524 10 78; + 632 544 84 00; local 2311 Notruf - SA - : + 966 146 77 353, + 966 3 8155 646; Ext. 280, 282, 283 Notruf - TH - : + 66 201 1086 Notruf - UAE - : 800 424 Notruf - ZA - : + 27 824 910 160

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS07

Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation.

· 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.



Page 3/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 8

Revision: 16.03.2021

(Contd. of page 2)

Trade name: BRUNOX® epoxy® - BULK

· Hazard pictograms



011002 011001

· Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P103 Read carefully and follow all instructions.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/ international regulations.

2.3 Other hazards

· Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

Bangereae componenter		
CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3 Reg.nr.: 01-2119457435-35- XXXX	1-methoxy-2-propanol	≥10-<20%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29- XXXX	2-methoxy-1-methylethyl acetate � Flam. Liq. 3, H226	10-25%

(Contd. on page 4) EU



Page 4/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021 Version number 8 Revision: 16.03.2021 Trade name: BRUNOX® epoxy® - BULK (Contd. of page 3) CAS: 67-63-0 ≥2.5-<10% propan-2-ol EINECS: 200-661-7 Flam. Liq. 2, H225 Index number: 603-117-00-0 Eye Irrit. 2, H319; STOT SE 3, H336 Reg.nr.: 01-2119457558-25-XXXX CAS: 67-64-1 acetone >2.5-<10% ♦ Flam. Liq. 2, H225
 ♦ Eye Irrit. 2, H319; STOT SE 3, H336 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-XXXX CAS: 112-34-5 2-(2-butoxyethoxy)ethanol >2.5-<10% EINECS: 203-961-6 Eye Irrit. 2, H319 Index number: 603-096-00-8 Reg.nr.: 01-2119475104-44-XXXX CAS: 64-18-6 formic acid ≥2.5-<10% EINECS: 200-579-1 Acute Tox. 3, H331 🚯 Skin Corr. 1C, H314 Index number: 607-001-00-0 Reg.nr.: 01-2119491174-37-Acute Tox. 4, H302 XXXX

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air. Do not leave affected persons unattended. Position and transport stably in side position. Seek medical treatment.

• After inhalation:

Take affected persons into fresh air and keep quiet.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. **After swallowing:**

- Rinse out mouth and then drink plenty of water.
- A person vomiting while laying on their back should be turned onto their side.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 5) EU



Page 5/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 8

Revision: 16.03.2021

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 4)

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** Formation of toxic gases is possible during heating or in case of fire. In case of fire, the following can be released: Carbon monoxide (CO)
- Carbon monoxide (CO)
- 5.3 Advice for firefighters
- Protective equipment:
 Do not inhale explosion cases

Do not inhale explosion gases or combustion gases. Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
 Ensure adequate ventilation
 Keep away from ignition sources.
 Wear protective equipment. Keep unprotected persons away.

 6.2 Environmental precautions:
 Do not allow product to reach sewage system or any water course.
 Inform respective authorities in case of seepage into water course or sewage system.
 Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up:
 Send for recovery or disposal in suitable receptacles.
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Ensure adequate ventilation.
 Do not flush with water or aqueous cleansing agents
 6.4 Reference to other sections
 See Section 7 for information on safe handling.
- See Section 7 for information on sale handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep receptacles tightly sealed. Store in cool, dry place in tightly closed receptacles. Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air). Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.



Page 6/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 8

Revision: 16.03.2021

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 5)

Information about fire - and explosion protection:

Highly volatile, flammable constituents are released during processing. Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

• 7.2 Conditions for safe storage, including any incompatibilities

- Storage:
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle. Store in a cool location.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep container tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 107-98-2 1-methoxy-2-propanol

IOELV Short-term value: 568 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Skin

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

IOELV Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin

CAS: 67-64-1 acetone

IOELV Long-term value: 1210 mg/m³, 500 ppm

CAS: 112-34-5 2-(2-butoxyethoxy)ethanol

IOELV Short-term value: 101.2 mg/m³, 15 ppm Long-term value: 67.5 mg/m³, 10 ppm

CAS: 64-18-6 formic acid

IOELV Long-term value: 9 mg/m³, 5 ppm

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.



Page 7/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 8

Revision: 16.03.2021

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 6)

Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

Respiratory protection:

Short term filter device: Filter A/P2

Filter AX

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Check the permeability prior to each anewed use of the glove.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

· Body protection: Solvent resistant protective clothing

SECTION 9: Physical and chemical properties

- <u>9.1 Information on basic physical and chemical properties</u>
- · General Information
- Appearance:
 - Form:
- Colour:
- · <u>Odour:</u>

Fluid Amber coloured Characteristic



Page 8/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 8

Revision: 16.03.2021

Trade name: BRUNOX® epoxy® - BULK

	(Contd. of page 7)
· Odour threshold:	Not determined.
· pH-value at 20 °C:	3.9
 <u>Change in condition</u> <u>Melting point/freezing point:</u> <u>Initial boiling point and boiling range</u> 	Undetermined. <u>::</u> 82 °C
· Flash point:	13 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	225 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
• Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <u>Explosion limits:</u> Lower: Upper:	1.5 Vol % 20 Vol %
· Vapour pressure at 20 °C:	12 hPa
 Density at 20 °C: Relative density Vapour density Evaporation rate 	0.99 g/cm ³ Not determined. Not determined. Not determined.
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.
 Partition coefficient: n-octanol/water: 	Not determined.
· <u>Viscosity:</u> <u>Dynamic:</u> <u>Kinematic:</u>	Not determined. Not determined.
<u>Solvent content:</u> Organic solvents: <u>Water:</u> VOC (EC)	45.9 % 27.3 % 45.90 %
Solids content:	1.5 %
• 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· **<u>10.1 Reactivity</u>** No further relevant information available.



Page 9/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 8

Revision: 16.03.2021

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 8)

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Forms explosive gas mixture with air.
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.
- Additional information:

As long as the prescribed application concentrations are maintained there is no danger that stable emulsions will form.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification: CAS: 107-98-2 1-methoxy-2-propanol Oral LD50 5,660 mg/kg (rat) LD50 13,000 mg/kg (rabbit) Dermal Inhalative LC50/4 h 6 mg/l (rat) CAS: 108-65-6 2-methoxy-1-methylethyl acetate Oral LD50 8,532 mg/kg (rat) LD50 Dermal >5,000 mg/kg (rat) Inhalative LC50/4 h 35.7 mg/l (rat) CAS: 67-63-0 propan-2-ol Oral LD50 5,045 mg/kg (rat) Dermal LD50 12,800 mg/kg (rabbit) Inhalative LC50/4 h 30 mg/l (rat) CAS: 67-64-1 acetone LD50 Oral 5,800 mg/kg (rat) LD50 Dermal >15,800 mg/kg (rat) 20,000 mg/kg (rabbit) Inhalative LC50/4 h 76 mg/l (rat) CAS: 112-34-5 2-(2-butoxyethoxy)ethanol Oral LD50 5,660 mg/kg (rat) Dermal LD50 4,000 mg/kg (rabbit) CAS: 64-18-6 formic acid Oral LD50 1,100 mg/kg (rat) Inhalative LC50/4 h 3 mg/l (ATE)



Page 10/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 8

Revision: 16.03.2021

Trade name: BRUNOX® epoxy® - BULK

- · Primary irritant effect:
- Skin corrosion/irritation
- Causes skin irritation. • Serious eye damage/irritation
- Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **<u>STOT-single exposure</u>** Based on available data, the classification criteria are not met.
- \cdot **<u>STOT-repeated exposure</u>** Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 107-98-2 1-methoxy-2-propanol

EC50 >500 mg/kg (daphnia)

LC50/96 h 4,600-10,000 mg/l (leuciscus idus)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

EC50 >500 mg/kg (daphnia)

LC50/96 h 160 mg/l (pimephales promelas)

CAS: 67-64-1 acetone

LC50/48 h 8,800 mg/l (daphnia)

CAS: 64-18-6 formic acid

EC50 120 mg/kg (daphnia)

LC50/48 h 122 mg/l (leuciscus idus)

- · 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.

(Contd. on page 11) EU

(Contd. of page 9)



Page 11/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 8

Revision: 16.03.2021

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 10)

SECTION 13: Disposal considerations

• **<u>12.6 Other adverse effects</u>** No further relevant information available.

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · European waste catalogue
- HP3 Flammable

HP4 Irritant - skin irritation and eye damage

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information	
<u>14.1 UN-Number</u> ADR/RID/ADN, IMDG, IATA	UN1866
 <u>14.2 UN proper shipping name</u> <u>ADR/RID/ADN</u> MDG, IATA 	1866 RESIN SOLUTION, special provision 640D RESIN SOLUTION
14.3 Transport hazard class(es)	
· ADR/RID/ADN, IMDG, IATA	
· <u>Class</u> · <u>Label</u>	3 Flammable liquids. 3
· <u>14.4 Packing group</u> · <u>ADR/RID/ADN, IMDG, IATA</u>	П
 <u>14.5 Environmental hazards:</u> <u>Marine pollutant:</u> 	No
 <u>14.6 Special precautions for user</u> <u>Hazard identification number (Kemler code)</u> <u>EMS Number:</u> <u>Stowage Category</u> 	Warning: Flammable liquids. 33 F-E, <u>S-E</u> B
 <u>14.7 Transport in bulk according to Annex II</u> of Marpol and the IBC Code 	Not applicable.
	(Contd. on page 12)



Page 12/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 8

Revision: 16.03.2021

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 11)

- · Transport/Additional information:
- · ADR/RID/ADN
- Limited quantities (LQ)
- Excepted quantities (EQ)
- Transport category
- Tunnel restriction code
- · IMDG
- Limited quantities (LQ)
- Excepted quantities (EQ)

· UN "Model Regulation":

5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2 D/E

5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

UN 1866 RESIN SOLUTION, SPECIAL PROVISION 640D, 3, II

SECTION 15: Regulatory information

- <u>15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture</u>
- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- <u>REGULATION (EC) No 1907/2006 ANNEX XVII</u> Conditions of restriction: 3, 55
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3)) None of the ingredients is listed.

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

CAS: 67-64-1 acetone

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

EU (Contd. on page 13)



Page 13/13

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2021

Version number 8

Revision: 16.03.2021

Trade name: BRUNOX® epoxy® - BULK

(Contd. of page 12)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H336 May cause drowsiness or dizziness.

Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations

Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids Category 2
- Flam. Liq. 3: Flammable liquids Category 3
- Acute Tox. 4: Acute toxicity Category 4 Acute Tox. 3: Acute toxicity Category 3
- Skin Corr. 1C: Skin corrosion/irritation Category 1C Skin Irrit. 2: Skin corrosion/irritation Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3
- ** Data compared to the previous version altered.