

Top Tec 4310 0W-30

Description

Sophisticated, low-ash low-friction motor oil for year-round use. The combination of synthetic technology and innovative additives provides outstanding protection against wear and reduces oil and fuel consumption while ensuring fast oil penetration of the engine. Various vehicle manufacturers require a motor oil with this specification for use with diesel particulate filters (DPF) to ensure the maximum service life of the DPF.

Properties

- enormous fuel saving
- rapid oil penetration
- suitable for diesel particulate filters
- excellent high-pressure and wear protection properties
- excellent corrosion protection
- smooth engine running
- excellent shear stability
- outstanding engine cleanliness
- miscible with all commercially available motor oils

Specifications / Approvals

ACEA C2 • Peugeot Citroen (PSA) B71 2312

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required

Fiat 9.55535-DS1 • Fiat 9.55535-GS1

Technical data

SAE class (engine oils)	0W-30 SAE J300
Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	50 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	9,5 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -35 °C (CCS)	≤ 6200 mPas ASTM D 5293
Viscosity index	175 DIN ISO 2909
HTHS at 150°C	≥ 2,9 mPas ASTM D 5481
Pour point	-39 °C DIN ISO 3016



Technical data

Evaporation loss (Noack)	10,9 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	7 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 g/100g DIN 51575
Color number (ASTM)	L 5,5 DIN ISO 2049

Areas of application

Ideal for the latest diesel and gasoline engines with and without multi-valve technology, turbocharging, charge air cooling and diesel particulate filter (DPF). In addition to various vehicles from PSA as well as Fiat, Alfa Romeo (TwinAir and MultiAir engines), can also in vehicles from other manufacturers that require a motor oil with this specification. Outstanding suitability for use in gas-driven passenger cars (CNG/LPG).

Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed.

Available pack sizes

1 l Canister plastic	2361 BOOKLET
5 l Canister plastic	2362 BOOKLET
20 l Canister plastic	3737 D-GB-I-E-P
60 l Black plate barrel	3738 D-GB
205 l Black plate barrel	3739 D-GB
1.000 l Container	21582 D-GB

Our information is based on thorough research

Product information

PI 34/10/10/2022



Top Tec 4310 0W-30

and may be considered reliable, although not
legally binding.