

#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.01.2022, Revision 27.01.2022

Version 05. Supersedes version: 04

Page 1 / 16

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

febi 101150 Engine Oil 5W-30

Article number: 101150, 101151, 101152, 101153, 101154

UFI: Q641-V918-Q00H-C01N

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Engine oil

1.2.2 Uses advised against

None known.

#### 1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG

Wilhelmstr. 47

58256 Ennepetal / GERMANY Phone +49 2333 911-0 Fax +49 2333 911-444 Homepage www.febi.com E-mail info@febi.com

Address enquiries to

Technical information info@febi.com
Safety Data Sheet info@febi.com

1.4 Emergency telephone number

**Advisory body** +49 (0)89-19240 (24h) (English)

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture [REGULATION (GB) CLP]

Skin Sens. 1: H317 May cause an allergic skin reaction.

2.2 Label elements

The product is required to be labelled in accordance with regulation CLP.

Hazard pictograms

**(!)** 

Signal word WARNING

Contains: C14-16-18 Alkyl phenol

**Hazard statements** H317 May cause an allergic skin reaction.

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P280 Wear protective gloves.

P333+P313 If skin irritation or rash occurs: Get medical advice / attention.

P501 Dispose of contents / container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of

disposal.

#### 2.3 Other hazards

Physico-chemical hazards No particular hazards known.

**Human health dangers** Frequent persistent contact with the skin can cause skin irritation.

**Environmental hazards** Does not contain any PBT or vPvB substances.

Other hazards Further hazards were not determined with the current level of knowledge.



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.01.2022, Revision 27.01.2022

Version 05. Supersedes version: 04

Page 2 / 16

#### **SECTION 3: Composition / Information on ingredients**

#### 3.1 Substances

not applicable

#### 3.2 Mixtures

#### The product is a mixture.

D 70/1	
Range [%]	Substance
30 - < 60	Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)
	CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 2,5	Paraffin oils (petroleum), catalytic dewaxed heavy
	CAS: 64742-70-7, EINECS/ELINCS: 265-174-4, EU-INDEX: 649-477-00-2, Reg-No.: 01-2119487080-42-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 2,5	Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract)
	CAS: 64742-56-9, EINECS/ELINCS: 265-159-2, Reg-No.: 01-2119480132-48-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 2,5	Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt)
	CAS: 64742-65-0, EINECS/ELINCS: 265-169-7, Reg-No.: 01-2119471299-27-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 2,5	Bis(nonylphenyl)amine
	CAS: 36878-20-3, EINECS/ELINCS: 253-249-4, Reg-No.: 01-2119488911-28-XXXX
	GHS/CLP: Aquatic Chronic 4: H413
1 - < 2,5	C14-16-18 Alkyl phenol
	CAS: -, EINECS/ELINCS: 931-468-2, Reg-No.: 01-2119498288-19-XXXX
	GHS/CLP: Skin Sens. 1B: H317 - STOT RE 2: H373
1 - < 2,5	Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)
	CAS: 93819-94-4, EINECS/ELINCS: 298-577-9, Reg-No.: 01-2119543726-33-XXXX
	GHS/CLP: Skin Irrit. 2: H315 - Eye Dam. 1: H318 - Aquatic Chronic 2: H411
	SCL [%]: > 12,5: Eye Dam. 1: H318, >10 - 12,5: Eye Irrit. 2: H319, >6,25 - 100: Skin Irrit. 2: H315

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.

For full text of H-statements and R-phrases: see SECTION 16.

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General information Change soaked clothing.

**Inhalation** Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

**Skin contact** In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

**Eye contact** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

**Ingestion** Consult a doctor immediately.

Rinse out mouth and give plenty of water to drink.

Do not induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

If swallowed or in the event of vomiting, risk of product entering the lungs.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Forward this sheet to your doctor.

# Safety Data Sheet (UK REACH) (GB)

# febi 101150 Engine Oil 5W-30 Article number 101150, 101151, 101152, 101153, 101154



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.01.2022, Revision 27.01.2022

Version 05. Supersedes version: 04

Page 3 / 16

#### **SECTION 5: Fire-fighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media foam, dry powder, water spray jet, carbon dioxide

Extinguishing media that must not

**not** Full water jet.

be used

#### 5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.

Carbon monoxide (CO) Sulphur oxides (SOx). Nitrogen oxides (NOx). Hydrogen sulfide ((H2S).

#### 5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

High risk of slipping due to leakage/spillage of product.

Forms slippery surfaces with water.

#### 6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

#### 6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. general-purpose binder). Dispose of absorbed material in accordance within the regulations.

### 6.4 Reference to other sections

See SECTION 8+13

#### **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Avoid formation of aerosols.

Do not smoke.

Fire class (DIN EN 2): B

Wash hands before breaks and after work.

Do not eat, drink or smoke when using this product.

Use barrier skin cream.

Take off contaminated clothing and wash before reuse.

Cloths contaminated with product should not be kept in trouser pockets.

# 7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with oxidizing agents.

Do not store together with food and animal food/diet.

Keep container tightly closed.

Protect from heat/overheating.



# Ferdinand Bilstein GmbH + Co. KG

Date printed 27.01.2022, Revision 27.01.2022

Version 05. Supersedes version: 04

Page 4 / 16

### 7.3 Specific end use(s)

See product use, SECTION 1.2



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.01.2022, Revision 27.01.2022

Version 05. Supersedes version: 04

Page 5 / 16

### SECTION 8: Exposure controls / personal protection

# 8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)

CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX

Long-term exposure: 5 mg/m³, oil mist

Short-term exposure (15-minute): 10 mg/m³

#### **DNEL**

Substance		
Bis(nonylphenyl)amine, CAS: 36878-20-3		
Industrial, dermal, Long-term - systemic effects, 5 mg/kg bw/day		
general population, dermal, Long-term - systemic effects, 2,5 mg/kg bw/day		
general population, oral, Long-term - systemic effects, 0,25 mg/kg bw/day		
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7		
Industrial, dermal, Long-term - systemic effects, 970 μg/kg bw/day		
Industrial, inhalative, Long-term - local effects, 5.58 mg/m³		
Industrial, inhalative, Long-term - systemic effects, 2.73 mg/m³		
general population, inhalative, Long-term - local effects, 1.19 mg/m³		
general population, oral, Long-term - systemic effects, 740 μg/kg bw/day		
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9		
Industrial, dermal, Long-term - systemic effects, 0,97 mg/kg bw/day		
Industrial, inhalative, Long-term - local effects, 5,58 mg/m³		
Industrial, inhalative, Long-term - systemic effects, 2,73 mg/m³		
general population, oral, Long-term - systemic effects, 0,74 mg/kg bw/day		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0		
worker, inhalative, Long-term - systemic effects, 2.73 mg/m³		
worker, inhalative, Long-term - local effects, 5.58 mg/m³		
worker, dermal, Long-term - systemic effects, 970 μg/kg bw/day		
general population, inhalative, Long-term - local effects, 1.19 mg/m³		
general population, oral, Long-term - local effects, 740 μg/kg bw/day		
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4		
Industrial, inhalative, Long-term - systemic effects, 8,31 mg/m³		
Industrial, dermal, Long-term - systemic effects, 0,58 mg/kg bw/day		
general population, dermal, Long-term - systemic effects, 0,29 mg/kg bw/day		
general population, inhalative, Long-term - systemic effects, 2,11 mg/m³		
general population, oral, Long-term - systemic effects, 0,24 mg/kg bw/day		
Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7		
Industrial, inhalative, Long-term - local effects, 5.6 mg/m³		
Industrial, inhalative, Long-term - systemic effects, 2.7 mg/m³		
Industrial, dermal, Long-term - systemic effects, 1 mg/kg bw/day		
general population, oral, Long-term - systemic effects, 0.74 mg/kg bw/day		
C14-16-18 Alkyl phenol, CAS: 1190625-94-5		
Industrial, inhalative, Long-term - systemic effects, 1,17 mg/m³		



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.01.2022, Revision 27.01.2022

Version 05. Supersedes version: 04

Page 6 / 16

#### **PNEC**

Industrial, dermal, Long-term - systemic effects, 300 µg/kg bw/d Substance Bis(nonylphenyl)amine, CAS: 36878-20-3 seawater, 41.2 µg/L sediment (freshwater), 1 mg/kg sediment dw sediment (seawater), 0.1 mg/kg sediment dw freshwater, 412 µg/L Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7 oral (food), 9,33 mg/kg Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9 oral (food), 9,33 mg/kg food Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0 oral (food), 9,33 mg/kg food Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4 oral (food), 10,67 mg/kg freshwater, 0,004 mg/l seawater, 0,004 mg/l sewage treatment plants (STP), 100 mg/l sediment (freshwater), 0,012 mg/kg dw soil, 0,005 mg/kg sediment (seawater), 0,001 mg/kg dw Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7 oral (food), 9.33 mg/kg food C14-16-18 Alkyl phenol, CAS: 1190625-94-5 oral (food), 3,3 mg/kg freshwater, 100 µg/l seawater, 10 µg/l sewage treatment plants (STP), 100 mg/l sediment (freshwater), 4266,16 mg/kg dw sediment (seawater), 426,62 mg/kg dw

#### 8.2 Exposure controls

Additional advice on system design 
Ensure adequate ventilation on workstation.

Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

**Eye protection** Safety glasses. (EN 166:2001)

Hand protection The details concerned are recommendations. Please contact the glove supplier for further

information.

> 0,11 mm: Nitrile rubber, >480 min (EN 374-1/-2/-3).

**Skin protection** Light protective clothing.

soil, 852,58 mg/kg dw

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Avoid contact with eyes and skin.

**Respiratory protection** Breathing apparatus in the event of aerosol or mist formation.

Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)

Thermal hazards No information available.

Delimitation and monitoring of the

environmental exposition

Comply with applicable environmental regulations limiting discharge to air, water and soil.



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.01.2022, Revision 27.01.2022

#### Version 05. Supersedes version: 04

#### Page 7 / 16

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical stateliquidColorlight brownOdorcharacteristic

Odour threshold No information available.

pH-value not applicable

pH-value [1%] No information available.
Boiling point [°C] No information available.
Flash point [°C] > 195 (ISO 2592)
Flammability (solid, gas) [°C] not applicable

Lower explosion limitNo information available.Upper explosion limitNo information available.

Oxidising properties no

Vapour pressure/gas pressure [kPa] <0,01 (20°C)

**Density [g/cm³]** ca. 0,85 (DIN 51757) (15 °C / 59,0 °F)

Relative density not determined

Bulk density [kg/m³] not applicable

Solubility in water virtually insoluble

Solubility other solvents No information available.

Partition coefficient [n-octanol/water] No information available.

Kinematic viscosity ca. 10,2 mm<sup>2</sup>/s (100°C) (DIN 51562/T1)

> 20,5 mm<sup>2</sup>/s (40°C)

Relative vapour densityNo information available.Evaporation speedNo information available.Melting point [°C]< -36 (DIN ISO 3016)</th>Auto-ignition temperatureNo information available.

**Decomposition temperature [°C]** > 65°C

Particle characteristics No information available.

9.2 Other information

Pour point: ca. -36°C

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

See SECTION 10.3.

### 10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

#### 10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents.

#### 10.4 Conditions to avoid

Strong acids.

Strong heating, because the thermal decomposition starts from > 65°C.



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.01.2022, Revision 27.01.2022

Version 05. Supersedes version: 04

Page 8 / 16

#### 10.5 Incompatible materials

Oxidizing agent Acids Strong basic compounds

#### 10.6 Hazardous decomposition products

In the case of heating following (decomposition) products may occure: Hydrogen sulfide (H2S).



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.01.2022, Revision 27.01.2022

Version 05. Supersedes version: 04

Page 9 / 16

# **SECTION 11: Toxicological information**

# 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute oral toxicity

Substance	
Bis(nonylphenyl)amine, CAS: 36878-20-3	
LD50, oral, Rat, 5000 mg/kg bw	
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7	
LD50, oral, Rat, 5000 mg/kg bw	
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9	
LD50, oral, Rat, >5000 mg/kg bw (OECD 401)	
NOAEL, oral, Rat, >1000 mg/kg bw (OECD 421)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0	
LD50, oral, Rat, 5000 mg/kg bw	
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4	
LD50, oral, Rat, 2600 mg/kg	
Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7	
LD50, oral, Rat, >5000 mg/kg bw (OECD 401)	
C14-16-18 Alkyl phenol, CAS: 1190625-94-5	
LD50, oral, Rat (female), >2000 mg/kg bw	

#### Acute dermal toxicity

#### Acute inhalational toxicity

Substance  Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7	
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7	
LC50, inhalative, Rat, 2.18 - 5.53 mg/L air, 4h	
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9	
LC50, inhalative, Rat, >5,53 mg/l air (OECD 403)	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0	
LC50, inhalative, Rat, 2,18 - 5,53 mg/L air, 4h	
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4	
LC50, inhalative, Rat, >2 mg/l	
Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7	



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.01.2022, Revision 27.01.2022

Version 05. Supersedes version: 04

Page 10 / 16

LC50, inhalative, Rat, 2.18 mg/l air (OECD 403)

Serious eye damage/irritation Toxicological data of complete product are not available.

CAS 93819-94-4: >10% - <12,5% Eye Irrit. 2 No classification.

Classification was carried out based on substance-specific concentration limits.

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

no adverse effect observed

Skin corrosion/irritation Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

no adverse effect observed

**Respiratory or skin sensitisation** Toxicological data of complete product are not available.

May cause an allergic skin reaction.

Calculation method

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

no adverse effect observed

Specific target organ toxicity — Based on the available information, the classification criteria are not fulfilled.

single exposure

**Specific target organ toxicity** — Based on the available information, the classification criteria are not fulfilled.

repeated exposure

.

based on the available information, the classification chiefla are not ruilliled.

Substance

Bis(nonylphenyl)amine, CAS: 36878-20-3

NOEL, oral, Rat, 100 mg/kg bw/day

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

NOAEL, dermal, Rabbit, 1000 mg/kg bw/day

NOAEL, dermal, Rat, 30 - 2000 mg/kg bw/day

NOAEC, inhalative, Rat, 980 mg/m³ air

LOAEL, oral, Rat, 125 mg/kg bw/day

Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9

NOAEC, inhalative, Rat, 980 mg/m³, no adverse effect observed

LOAEL, oral, Rat, 125 mg/kg bw/day, adverse effect observed

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

NOAEL, dermal, Rabbit, 1000 mg/kg bw/day

NOAEL, inhalative, Rat, 980 mg/m³ air

LOAEL, oral, Rat, 125 mg/kg bw/day

C14-16-18 Alkyl phenol, CAS: 1190625-94-5

NOAEL, oral, Rat, 30 - 100 mg/kg bw/day

Mutagenicity

Based on the available information, the classification criteria are not fulfilled.

Substance

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

in vitro, negativ

Reproduction toxicity

Based on the available information, the classification criteria are not fulfilled.

Substance



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.01.2022, Revision 27.01.2022

Version 05. Supersedes version: 04

Page 11 / 16

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed

Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9

NOAEL, oral, Rat, 1000 mg/kg bw/day, In vivo study, negativ

Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0

NOAEL, oral, Rat, 1000 mg/kg bw/d (Effect on fertility), no adverse effect observed

Carcinogenicity Based on the available information, the classification criteria are not fulfilled.

**Aspiration hazard** Based on the available information, the classification criteria are not fulfilled.

General remarks

Toxicological data of complete product are not available.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.

11.2 Information on other hazards

Endocrine disrupting properties

Other information

No information available.



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.01.2022, Revision 27.01.2022

Version 05. Supersedes version: 04

Page 12 / 16

# **SECTION 12: Ecological information**

# 12.1 Toxicity

Substance		
Bis(nonylphenyl)amine, CAS: 36878-20-3		
EC50, (48h), Invertebrates, 100 mg/L		
EL50, (72h), Algae, 100 mg/L		
NOELR, (21d), Invertebrates, 4.45 mg/L		
NOELR, (33d), fish, 10 mg/L		
Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7		
EL50, (48h), Invertebrates, 10 g/L		
NOELR, (14d), fish, 1 mg/L		
LL50, (96h), fish, 100 mg/L		
LL50, (96h), Invertebrates, 10 g/L		
Distillates (petroleum), solvent-dewaxed light paraffinic (containing < 3% DMSO-extract), CAS: 64742-56-9		
EL50, (24h), Daphnia magna, >10000 mg/l (OECD 202)		
LL50, (96h), Pimephales promelas, >100 mg/l (OECD 203)		
NOEL, (72h), Pseudokirchneriella subcapitata, >100 mg/l (OECD 201)		
NOEL, (21d), Daphnia magna, 10 mg/l (OECD 211)		
Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3% DMSO Extrakt), CAS: 64742-65-0		
NOELR, (14d), fish, 1 g/L		
LL50, (96h), fish, 100 mg/L		
LL50, (96h), Invertebrates, 10 g/L		
Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate), CAS: 93819-94-4		
EC50, (3h), Activated sludge, >10000 mg/l		
EC50, (72h), Selenastrum capricornutum, 2,1 mg/l		
EC50, (48h), Daphnia magna, 5,4 mg/l (OECD 202)		
IC50, (21d), Daphnia magna, >0,8 mg/l		
LL50, (96h), Oncorhynchus mykiss, 4,5 mg/l		
Paraffin oils (petroleum), catalytic dewaxed heavy, CAS: 64742-70-7		
EL50, (24h), Daphnia magna, >10000 mg/l (OECD 202)		
LL50, (96h), Pimephales promelas, >100 mg/l (OECD 203)		
NOEL, (72h), Pseudokirchneriella subcapitata, >100 mg/l (OECD 201)		
NOEL, (21d), Daphnia magna, >10 mg/l (OECD 211)		
C14-16-18 Alkyl phenol, CAS: 1190625-94-5		
LC50, (96h), Cyprinus carpio, >100 mg/l		
EC50, (72h), Pseudokirchneriella subcapitata, >100 mg/l		
EC50, (24h), Daphnia magna, >100 mg/l		
NOEC, (72h), Pseudokirchneriella subcapitata, 100 mg/l		
NOELR, (24h), Daphnia magna, >100 mg/l		

# 12.2 Persistence and degradability

Behaviour in environment

compartments

not determined

Behaviour in sewage plant

Can be separated out mechanically in purification plants.

Biological degradability Th

The product is not readily biodegradable.



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.01.2022, Revision 27.01.2022

Version 05. Supersedes version: 04

Page 13 / 16

#### 12.3 Bioaccumulative potential

No information available.

#### 12.4 Mobility in soil

No information available.

#### 12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

#### 12.6 Endocrine disrupting properties

No information available.

#### 12.7 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.

The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

#### Product

Coordinate disposal with the authorities if necessary.

Disposal in an incineration plant in accordance with the regulations of the local authorities.

In according to RoHS!

Waste no. (recommended) 130205\* mineral-based non-chlorinated engine, gear and lubricating oils

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended) 150110\* packaging containing residues of or contaminated by hazardous substances

#### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with no

**IMDG** 

not applicable

Air transport in accordance with IATA not applicable



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.01.2022, Revision 27.01.2022

Version 05. Supersedes version: 04

Page 14 / 16

14.2 UN proper shipping name

Transport by land according to

ADR/RID

NO DANGEROUS GOODS

Inland navigation (ADN)

NO DANGEROUS GOODS

**IMDG** 

Marine transport in accordance with NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

14.3 Transport hazard class(es)

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN)

not applicable

Marine transport in accordance with not applicable

**IMDG** 

Air transport in accordance with IATA not applicable

14.4 Packing group

Transport by land according to

not applicable

ADR/RID

**IMDG** 

Inland navigation (ADN)

not applicable

Marine transport in accordance with not applicable

Air transport in accordance with IATA not applicable

14.5 Environmental hazards

Transport by land according to

ADR/RID

no

Inland navigation (ADN)

no

Marine transport in accordance with no

**IMDG** 

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Maritime transport in bulk according to IMO instruments

not applicable



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.01.2022, Revision 27.01.2022

Version 05. Supersedes version: 04

Page 15 / 16

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EEC-REGULATIONS 2008/98/EC 2000/532/EC); 2010/75/EU; 2004/42/EC; (EC) 648/2004; (EC) 1907/2006

(REACH); (EU) 1272/2008; 75/324/EEC ((EC) 2016/2037); (EU) 2020/878; (EU) 2016/131;

(EU) 517/2014

**TRANSPORT-REGULATIONS** ADR (2021); IMDG-Code (2021, 40. Amdt.); IATA-DGR (2021)

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011); UK

REACH; GB CLP.

- Observe employment restrictions

for people

Observe employment restrictions for mothers-to-be and nursing mothers. Observe

employment restrictions for young people.

- VOC (2010/75/CE) not applicable

#### 15.2 Chemical safety assessment

For this product a chemical safety assessment has not been carried out.

#### **SECTION 16: Other information**

#### 16.1 Hazard statements (SECTION 3)

H413 May cause long lasting harmful effects to aquatic life.

H373 May cause damage to organs through prolonged or repeated exposure.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

H318 Causes serious eye damage. H315 Causes skin irritation.

H304 May be fatal if swallowed and enters airways.



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 27.01.2022, Revision 27.01.2022

Version 05. Supersedes version: 04

Page 16 / 16

#### 16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

ATE = acute toxicity estimate CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level

DNEL = Derived No Effect Level

EC50 = Median effective concentration ECB = European Chemicals Bureau

EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

EL50 = Median effective loading

ELINCS = European List of Notified Chemical Substances

EmS = Emergency Schedules

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods

IUCLID = International Uniform ChemicaL Information Database

IVIS = In vitro irritation score

LC50 = Lethal concentration, 50%

LD50 = Median lethal dose

LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

LL50 = Median lethal loading

LQ = Limited Quantities

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance

PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value – time-weighted average TLV®STEL = Threshold limit value – short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

#### 16.3 Other information

Classification procedure Skin Sens. 1: H317 May cause an allergic skin reaction. (Calculation method)

Modified position SECTION 3 been added: Paraffin oils (petroleum), catalytic dewaxed heavy

SECTION 3 been added: Distillates (petroleum), solvent-dewaxed light paraffinic (containing <

3% DMSO-extract)

SECTION 3 been added: Distillates (petroleum), solvent-dewaxed heavy paraffinic (< 3%

DMSO Extrakt)