

Page 1 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 13.10.2020 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

DFI Cleaner

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

DFI Cleaner

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Additive

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Tel.: (+49) 0731-1420-0

Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

+1 872 5888271 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Acute Tox.	4	H302-Harmful if swallowed.
Skin Irrit.	2	H315-Causes skin irritation.
Eye Dam.	1	H318-Causes serious eye damage.
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Acute	1	H400-Very toxic to aquatic life.
Aquatic Chronic	1	H410-Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Page 2 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008 Replacing version dated / version: 13.10.2020 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

DFI Cleaner



Danger

H302-Harmful if swallowed. H315-Causes skin irritation. H318-Causes serious eye damage. H304-May be fatal if swallowed and enters airways. H336-May cause drowsiness or dizziness. H410-Very toxic to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves / eye protection / face protection.

P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P331-Do NOT induce vomiting. P332+P313-If skin irritation occurs: Get medical advice / attention.

P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

Poly[oxy(1,2-propanediyl)], .alpha.-propyl-.omega.-hydroxy-, C12-15 alkyl ethers

Distillates (petroleum), hydrotreated light

Hydrocarbons, C10, aromatics, >1% naphthalene

Poly[oxy(1,2-propanediyl)], .alpha.-(3-aminopropyl)-.omega.-hydroxy-, C12-15 alkyl ethers

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

Dangerous vapours heavier than air.

In case of spreading near the ground, flashback to distance sources of ignition is possible.

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. **3.2 Mixtures**

Distillates (petroleum), hydrotreated light	
Registration number (REACH)	01-2119484819-18-XXXX
Index	649-422-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	265-149-8
CAS	64742-47-8
content %	40-50
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Irrit. 2, H315
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Poly[oxy(1,2-propanediyl)], .alpha(3-aminopropyl)omegahydroxy-,	
C12-15 alkyl ethers	
Registration number (REACH)	
Index	



GB)

Page 3 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 13.10.2020 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

DFI Cleaner

EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	
content %	32,88-36,18
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Acute Tox. 4, H302
	Skin Irrit. 2, H315
	Eye Dam. 1, H318
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)
Specific Concentration Limits and ATE	Eye Dam. 1, H318: >=36,19 %
	Eye Irrit. 2, H319: >=32,88 %

Phenol, (dimethylamino)methyl-, polyisobutylene derivatives	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	
content %	5-10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Aquatic Chronic 3, H412

Poly[oxy(1,2-propanediyl)], .alphapropylomegahydroxy-, C12-15	
alkyl ethers	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	
content %	1-<3
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Skin Irrit. 2, H315
	Eye Dam. 1, H318
Specific Concentration Limits and ATE	Eye Dam. 1, H318: >=10,0001 %
	Eye Irrit. 2, H319: >=5 %

Hydrocarbons, C10, aromatics, >1% naphthalene	
Registration number (REACH)	01-2119463588-24-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	919-284-0
CAS	(64742-94-5)
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066
	STOT SE 3, H336
	Asp. Tox. 1, H304
	Aquatic Chronic 2, H411

Naphthalene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	601-052-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	202-049-5
CAS	91-20-3
content %	0,1-<0,25
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Sol. 2, H228
	Acute Tox. 4, H302
	Carc. 2, H351
	Aquatic Acute 1, H400 (M=1)
	Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!



(B)

Page 4 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 13.10.2020 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

DFI Cleaner

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Protect uninjured eye.

Follow-up examination by an ophthalmologist.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting. Consult doctor immediately.

Danger of aspiration.

In case of vomiting, keep head low so that the stomach content does not reach the lungs.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

eyes, reddened

watering eyes

Drying of the skin.

Dermatitis (skin inflammation)

Ingestion:

Nausea

Vomiting

Danger of aspiration.

Oedema of the lungs

Chemical pneumonitis (condition similar to pneumonia)

Repeated exposure may cause skin dryness or cracking.

Dermatitis (skin inflammation)

Irritation of the respiratory tract

4.3 Indication of any immediate medical attention and special treatment needed

Gastric lavage (stomach washing) only under endotracheal intubation.

Subsequent observation for pneumonia and pulmonary oedema.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Danger of bursting (explosion) when heated

Explosive vapour/air or gas/air mixtures.

Oxides of carbon

Aldehydes

Ammonia

Nitro gases

Amines

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.



Œ

Page 5 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 13.10.2020 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

DFI Cleaner

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Keep unprotected persons away.

Ensure sufficient supply of air.

Remove possible causes of ignition - do not smoke.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

Resolve leaks if this possible without risk.

If leakage occurs, dam up.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13. Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Do not breathe vapour/spray.

Keep away from sources of ignition - Do not smoke.

Avoid contact with eyes or skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

Do not use on hot surfaces.

Use as far as possible in closed circuit plants/systems.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Under all circumstances prevent penetration into the soil.

Store in a well ventilated place.

Store cool.

Store in a dry place.

7.3 Specific end use(s)



③B)·

Page 6 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 13.10.2020 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

DFI Cleaner

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 800 mg/m3

Chemical Name	Distillates (petrol	eum), hydrotreated light			Content %:40-50				
WEL-TWA: 800 mg/m3		WEL-STEL:							
Monitoring procedures:	Monitoring procedures: - Draeger - Hydrocarbons 0,1%/c (81 03 571)								
	- Draeger - Hydrocarbons 2/a (81 03 581)								
	- Compur - KITA-187 S (551 174)								
BMGV:			Other information: (O paragraphs 84-87, EH4		o RCP-method,				
Chemical Name	Hydrocarbons, C	10, aromatics, >1% naphthalene			Content %:1-<2,5				
WEL-TWA: 500 mg/m3 (Aromatics	5)	WEL-STEL:							
Monitoring procedures:	-	Draeger - Hydrocarbons 0,1%/c (81	l 03 571)						
	-	Draeger - Hydrocarbons 2/a (81 03	581) ´						
BMGV:		,	Other information:						
® .					Content %:0,1-				
Chemical Name	Naphthalene				<0,25				
WEL-TWA: 500 mg/m3 (Aromatics	s) (WEL), 10 ppm	WEL-STEL:			,				
(50 mg/m3) (EU)	, , , , , , , , , , , , , , , , , , , ,								
Monitoring procedures:	-	Compur - KITA-153 U(C) (551 182)	1						
	_	NIOSH 5506 (POLYNUCLEAR AR		NS by H	PLC) - 1998				
	-	NIOSH 5515 (POLYNUCLEAR AR							
	-	OSHA 35 (Napthalene) - 1982		, -	-,				
BMGV:			Other information:						
· ·	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·	·						

Hydrocarbons, C10, aromatics, >1% naphthalene							
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note	
Consumer	Human - dermal	Long term, systemic effects	DNEL	7,5	mg/kg bw/d		
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m3		
Consumer	Human - oral	Long term, systemic effects	DNEL	7,5	mg/kg bw/d		
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	151	mg/m3		
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	12,5	mg/kg bw/d		
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	151	mg/m3		

Naphthalene							
Area of application	Exposure route /	Effect on health	Descriptor	Value	Unit	Note	
	Environmental						
	compartment						
	Environment - freshwater		PNEC	0,0024	mg/l		
	Environment - marine		PNEC	0,0024	mg/l		
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	25	mg/m3		
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	3,57	mg/kg bw/day		



Page 7 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 13.10.2020 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

DFI Cleaner

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Recommended

Protective Neoprene® / polychloroprene gloves (EN ISO 374).

Protective nitrile gloves (EN ISO 374).

Minimum layer thickness in mm:

0,35

Permeation time (penetration time) in minutes:

240 - >480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Ensure sufficient ventilation.

If OES or MEL is exceeded.

Filter A P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.



Page 8 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 13.10.2020 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

DFI Cleaner

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:

Colour:

Odour:

Melting point/freezing point:

Boiling point or initial boiling point and boiling range:

Flammability:

Lower explosion limit:

Upper explosion limit:

Flash point:

Auto-ignition temperature:

Decomposition temperature:

Kinematic viscosity:

Solubility:

Partition coefficient n-octanol/water (log value):

Vapour pressure:

Density and/or relative density: Relative vapour density:

Particle characteristics:

9.2 Other information

Explosives: Oxidising liquids:

Light yellow, Transparent

There is no information available on this parameter. There is no information available on this parameter.

There is no information available on this parameter.

Flammable

There is no information available on this parameter. There is no information available on this parameter.

74 °C (Pensky-Martens, closed cup)

There is no information available on this parameter. There is no information available on this parameter.

Mixture is non-soluble (in water).

12,5 mm2/s (40°C)

Insoluble

Does not apply to mixtures.

There is no information available on this parameter.

0,886 g/ml (15°C)

There is no information available on this parameter.

Does not apply to liquids.

There is no information available on this parameter. There is no information available on this parameter.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with strong alkalis.

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

See also section 5.2

Ammonia

Amines

Glycol

Alcohols

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).



(B)

Page 9 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 13.10.2020 $\,/\,0007$

Valid from: 01.11.2021 PDF print date: 01.11.2021

DFI Cleaner

DFI Cleaner						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-RE):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Distillates (petroleum), hydrotr	Distillates (petroleum), hydrotreated light									
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes				
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat						
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit						
Acute toxicity, by inhalation:	LD50	>5	mg/l/4h	Rat						
Skin corrosion/irritation:						Irritant				
Serious eye damage/irritation:						Mild irritant				
Respiratory or skin						No (skin contact)				
sensitisation:										
Aspiration hazard:						Yes				

Hydrocarbons, C10, aromatics, >1% naphthalene							
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit			
Acute toxicity, by inhalation:	LC50	>590	mg/m3	Rat		Vapours	
Aspiration hazard:						Yes	

Naphthalene Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	533-710	mg/kg	Mouse	OECD 401 (Acute Oral	110000
, , , , , , , , , , , , , , , , , , ,			3 3		Toxicity)	
Acute toxicity, by dermal route:	LD50	>16000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>44	mg/l/4h	Rat	OECD 403 (Acute	Maximum
					Inhalation Toxicity)	achievable
						concentration.
Skin corrosion/irritation:				Rabbit		Not irritant
Serious eye damage/irritation:				Rabbit	(Draize-Test)	Not irritant
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative
				typhimurium	Reverse Mutation Test)	
Germ cell mutagenicity:				Mammalian	OECD 479 (Genetic	Negative
					Toxicology - In Vitro	
					Sister Chromatid	
					Exchange assay in	
					Mammalian Cells)	
Reproductive toxicity				Rat	OECD 414 (Prenatal	Negative
(Developmental toxicity):					Developmental Toxicity	
					Study)	

11.2. Information on other hazards

DFI Cleaner						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes



B.

Page 10 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 13.10.2020 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

DFI Cleaner

Endocrine disrupting properties:	Does not apply
	to mixtures.
Other information:	No other
	relevant
	information
	available on
	adverse effects
	on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

DFI Cleaner							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse							No information
effects:							available on other adverse effects on the environment.

Distillates (petroleum), hydrotreated light								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to daphnia:	EC50	48h	1,4	mg/l	Daphnia magna			
12.1. Toxicity to fish:	NOEC/NOEL	28d	0,098	mg/l	Oncorhynchus mykiss			
12.1. Toxicity to algae:	EL50	72h	3	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)		
12.2. Persistence and degradability:		28d	58,6	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Analogous conclusion	

Phenol, (dimethylamino)methyl-, polyisobutylene derivatives									
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes		
12.1. Toxicity to fish:	LC50	96h	31	mg/l	Pimephales				
					promelas				
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna				
12.1. Toxicity to algae:	EC50	96h	>450	mg/l	Pseudokirchneriell				
					a subcapitata				
12.2. Persistence and	DOC	28d	20,7	%	activated sludge		Inherent		
degradability:									
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge				

Hydrocarbons, C10, aromatics, >1% naphthalene								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.3. Bioaccumulative potential:	Log Pow		3,3					
12.1. Toxicity to fish:	LC50	96h	2-5	mg/l	Pimephales promelas			



Œ

Page 11 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 13.10.2020 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

DFI Cleaner

12.1. Toxicity to daphnia:	EC50	48h	3-10	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	1 - 3	mg/l	Pseudokirchneriell a subcapitata		
12.2. Persistence and degradability:		28d	58	%	,	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Inherent
12.3. Bioaccumulative potential:	BCF		<100				Low

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,11	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LC50	27d	0,12	mg/l	Oncorhynchus mykiss	·	
12.3. Bioaccumulative potential:	BCF		36,5-168				Low
12.1. Toxicity to daphnia:	EC50	48h	2,16	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	>60d	0,59	mg/l	Daphnia pulex		125d
12.1. Toxicity to algae:	EC50	96h	2,96	mg/l	Pseudokirchneriell a subcapitata		
12.2. Persistence and degradability:		28d	>74	%		OECD 301 C (Ready Biodegradability - Modified MITI Test (I))	Readily biodegradable
12.2. Persistence and degradability:		28d	0-2	%	activated sludge	OECD 302 C (Inherent Biodegradability - Modified MITI Test (II))	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		3,4			OECD 107 (Partition Coefficient (n- octanol/water) - Shake Flask Method)	(25°C)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

13 07 03 other fuels (including mixtures)

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.



Page 12 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 13.10.2020 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

DFI Cleaner

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number or ID number: 3082

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (POLYETHER AMINE, DISTILLATES

(PETROLEUM))

14.3. Transport hazard class(es): 14.4. Packing group: Ш Classification code: M6 LQ: 5 L

14.5. Environmental hazards: environmentally hazardous

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (POLYETHER AMINE, DISTILLATES (PETROLEUM))

14.3. Transport hazard class(es): 14.4. Packing group: Ш F-A, S-F EmS:

Marine Pollutant: Yes

14.5. Environmental hazards: environmentally hazardous

Transport by air (IATA)

14.2. UN proper shipping name:

Environmentally hazardous substance, liquid, n.o.s. (POLYETHER AMINE, DISTILLATES (PETROLEUM))

14.3. Transport hazard class(es): 9 Ш

14.4. Packing group:

14.5. Environmental hazards: environmentally hazardous

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered

according to storage, handling etc.)):		
Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
_		dangerous substances as	dangerous substances as
			referred to in Article 3(10) for the
		application of - Lower-tier	application of - Upper-tier
		requirements	requirements
F1		100	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.











Page 13 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 13.10.2020 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

DFI Cleaner

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

1-16

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation	Evaluation method used
(EC) No. 1272/2008 (CLP)	
Acute Tox. 4, H302	Classification based on toxicological analyses.
Skin Irrit. 2, H315	Classification according to calculation procedure.
Eye Dam. 1, H318	No classification based on test data.
Asp. Tox. 1, H304	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Acute 1, H400	Classification according to calculation procedure.
Aquatic Chronic 1, H410	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

H228 Flammable solid.

EUH066 Repeated exposure may cause skin dryness or cracking.

Acute Tox. — Acute toxicity - oral Skin Irrit. — Skin irritation

Eye Dam. — Serious eye damage

Asp. Tox. — Aspiration hazard STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aquatic Acute — Hazardous to the aquatic environment - acute

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Flam. Sol. — Flammable solid

Carc. — Carcinogenicity

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).



Page 14 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 13.10.2020 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

DFI Cleaner

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the

International Carriage of Dangerous Goods by Road)

Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

Acute Toxicity Estimate ATE

Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany) BAM

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

body weight bw

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level DNEL Derived No Effect Level DOC Dissolved organic carbon

dw dry weight

for example (abbreviation of Latin 'exempli gratia'), for instance e.a.

EbCx, EyCx, EbLx (x = 10, 50)Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

European Community EC ECHA European Chemicals Agency ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100)

Effect Concentration/Level for x % effect EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

European List of Notified Chemical Substances **ELINCS**

FN European Norms

United States Environmental Protection Agency (United States of America) **EPA**

ErCx, $E\mu Cx$, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

et cetera etc. ΕU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number general gen.

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

Adsorption coefficient of organic carbon in the soil Koc

octanol-water partition coefficient Kow

International Agency for Research on Cancer IARC IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

including, inclusive incl.

IUCLID International Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ

Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

not applicable n.a. not available n.av.



Page 15 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0008

Replacing version dated / version: 13.10.2020 / 0007

Valid from: 01.11.2021 PDF print date: 01.11.2021

DFI Cleaner

n.c. not checked n.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

organic org.

OSHA Occupational Safety and Health Administration (USA)

persistent, bioaccumulative and toxic PBT

PΕ Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million **PVC** Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Telephone Tel.

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.