


LEDinspect FLEXIBLE INSPECTION LIGHT



Fully flexible under bonnet inspection light

Place light exactly where you need it, even in tight spaces



Bright light output

Choose between 1000, 400 and 100 lumens output or red light for use at the rear of a vehicle



Long lasting battery life

Experience up to 3 hours (on high), 6.5 hours (on medium) and 20+ hours (on low) battery life. Recharging is easy thanks to the USB-C port.



Versatile fitting options

Features removable elasticated hooks and strong magnetic connections



Inspection lights are a vital part of any professional's toolbox. Under bonnet lamps provide bright light over a wide area to enable professionals to work with maximum visibility.

The LEDinspect FLEXIBLE INSPECTION LIGHT allows users to place light exactly where it is required. Our most versatile inspection light, it features removable elastic straps that allow the light to be fitted to areas as wide as 2.1m. The light strip is fully flexible, allowing the light to bend around the workspace. The rotating ends feature strong magnetic connections and USB-C charging.

Technical data

Product information

Application (Category and Product specific)	LED inspection lights
---	-----------------------

General Product Information

Global order reference	LEDIL416
------------------------	----------

Electrical Data

Nominal wattage	10 W
Nominal voltage	5.0 V

Photometric Data

Color temperature	6200-6500 K
Nominal luminous flux	1000 lm
Light color LED	White

Physical Attributes & Dimensions

Product weight	259.00 g
Length	1950 mm
Width	32.0 mm
Height	39.0 mm

LED module information

Number of LEDs per module	75
---------------------------	----

Lifetime Data

Guarantee	2 years
-----------	---------

Capabilities

Technology	LED
------------	-----

Certificates & standards

Standards	CE / EMC / MSDS / ROHS / UKCA
-----------	-------------------------------

Logistical data

Watt hour per battery	8.14
-----------------------	------

Environmental & Regulatory Information

Product datasheet


Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	01f2cf81-0802-463c-8c06-d58936072bea

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172405959	INSPECTION LAMP	Folding carton box 1	100 mm x 49 mm x 186 mm	0.91 dm ³	292.00 g
4062172405966	INSPECTION LAMP	Shipping carton box 6	220 mm x 165 mm x 250 mm	9.07 dm ³	1912.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	User instruction GPRS_Safety symbols instructions

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

