

MOTIP Bumper Paint

Technical Information



Quality & properties

- Excellent coverage
- Lasting colour and lasting gloss
- Maintains the original structure of the bumper
- Resistant to chemicals and weather influences
- Excellent adhesion

Repair and embellish the bumper of your car with MOTIP Bumper Paint. Bumper Paint has excellent coverage and adhesion to repair and embellish plastic bumpers, maintaining the original bumper structure. Bumper Paint offers a lasting colour and a lasting gloss. Bumper Paint is scratch-resistant and shock proof and is resistant to chemicals and the weather.

Ord.-no: 04073, 04074, 04075, 04076, 04085, 880115

Physical & chemical data

- Base: Alkyd resin
- Colourname:
 - black
 - middle grey
 - dark grey
 - anthracite
 - white
 - black glossy
- Smell: Characteristic
- Degree of gloss:
 - mat, 10 ±2
 - gloss, >75
- Efficiency: 400 ML – 2 Bumpers m²
- Dust dry: 20 - 30 min
- Dry to touch: 60 min
- Completely dry: 24 h
- Overcoatable: 24 h
- Surfaces: Plastic bumpers
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point:
 - n.a.
 - n.a. °C
- Temperature resistance: 110 °C
- Storage stability: 10 years
- Content: 400 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.

Pre Treatment: The surface must be clean, dry and free of grease.

Treatment: The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre. Apply the bumper spray in several thin layers, till the desired result has been achieved. Before applying the next layer, again shake the aerosol.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.